



PUMPS

ROTARY GEAR PUMPS

STAINLESS STEEL GEAR PUMPS

SELF PRIMING MUD PUMPS-GLAND TYPE

SELF PRIMING MUD PUMPS-SEAL TYPE

COUPLE DRIVE TRIPLEX PUMPS

TANK WITH TROLLEY DRIVE TRIPLEX PUMPS

CYLINDER & HOSE TEST PUMPS

VALVE & TUBE TEST PUMPS

BOILER FEED WATER PUMPS

STAINLESS STEEL CENTRIFUGAL PUMPS

CONTROL PANELS (FLP & NON FLP)

STARTERS (FLP & NON FLP)

ELECTRIC MOTORS (FLP & NON FLP)

Manufactured By:

EXCEL PUMPS PRIVATE LIMITED.
AHMEDABAD. INDIA

SELF PRIMING MUD PUMPS - SEAL TYPE

Mechanical Seal Type Self Priming Mud Pumps used in Drainage Applications such as Polluted liquids Pumping & drain out liquid waste from pits & canals.



Flow : 200 M3/hr (Max)
Head: 30 MTRS (Max)

COUPLE DRIVE TRIPLEX PUMPS

Applications where continuous high flow and high pressure pumping is essential & compact pump size is must.

Generally used for Reverse Osmosis. Materials used are either SS Ceramic Coated plunger with SS-316 head or complete Ceramic Plunger with bronze head.



Flow : 6 M3/hr (Max)
Pressure : 100 Bar (Max)

HIGH PRESSURE HYDRO-TEST PUMPS

Tailor Made assembled units incorporating high quality Triplex Plunger Pumps for Hydro-Testing of Pipelines, Pressure Vessels & Equipments subject to hydrotest



Pressure : 350
BarFlow : 21 LPM

FLANGE TYPE ROTARY GEAR PUMPS

Rotary Gear Pumps used for handling oils and viscous liquids for liquids having inherent lubricating property. Available in Materials of constructions like Standard CI , CI/SS, All SS, Bronze/SS or WCB/SS.



Flow : 120 M3/hr (Max)
Pressure : 11 Kg/Cm2 (Max)

TROLLEY DRIVE TRIPLEX PUMPS WITH TANK

High pressure Triplex plunger Pumps mounted on Heavy Duty MS fabricated base with superior quality wheels . Generally used for Hydraulic testing, Industrial Washing, Chemical Injection, Water Injection at High Pressure, Cleaning of Heat Exchanger, Boilers, Chemical Vessels etc. under High Pressure.



Flow : 30 M3/hr (Max)
Pressure : 450 Bar (Max)

Represented By:

Manufactured By:

EXCEL PUMPS PRIVATE LIMITED.

204, Mahashati Complex, Nr. Family Court,
Opp. Loha Bhavan, Navrangpura, Ahmedabad. INDIA

Ph.: +91-79-2754 2673

Cell : +91-9824036015, +91-9723823820, +91-9033066015

Web : www.excelpumps.in

E-mail : excelpumps@gmail.com



*PUMPS that
World NEEDS..!*



**QUALITY
Through
Innovation**

SELF PRIMING MUD PUMPS - GLAND TYPE

Self Priming Centrifugal Pumps for handling polluted liquids, public and civil engineering, de-watering and pumping out bilges. Standard material is Cast Iron. Other materials like CI/SS, All SS, Bronze/SS, Alloy-20



Flow : 640 M³/hr(Max)
Head: 46 MTRS (Max)

SUPREME PRESSURE PLUNGER PUMPS

Pumps for High flow and High pressure pumping is required.

Generally used in water well drilling & Special Duty Conditions. Field Replaceable Suction/Discharge Valve made from special materials.



Flow : 163 GPM (Max)
Pressure: 2800 Bar (Max)

STAINLESS STEEL CENTRIFUGAL PUMPS

Pumps having BACK PULL out design can handle clear water/liquids having temperature range - 50o C to + 300o C. Materials of construction offered Cast Iron, Ni-Resist, CI/SS, All SS, WCB/SS, Bronze/SS and Alloy-20.



Flow : 400 M³/hr (Max.)
Head : 125 MTRS (Max.)

BOILER FEED WATER PUMPS

Pumps for boiler feed applications, High Head water supply, Sprinkler irrigation, fire fighting and high head delivery can feed water temperature up to 80o C. Standard Material of construction comprise of Cast IRon Volute and Stage Casing with Bronze Impellers.



Flow: 34 M³/hr (Max)
Head: 330 MTRS (Max)

ELECTRIC DRIVE PRESSURE TEST PUMPS

Compact, Self Oiling design, Single or Three Plunger Hydro-Test Pumps are designed for long life. Used for Hydraulic Testing of Gas Cylinders, Pressure Hoses. Used by Original Equipment Manufacturers for high Pressure Applications.



Test Pressure:
15 Kg./Cm² to
1200 Kg./Cm²

Flow Capacity:
0.5 LPM to 30 LPM

MANUAL TEST PUMPS

Hand Operated Hydraulic Test Pumps used for Hydraulic testing of Valves, Tubes, Small Pressure Vessels, Castings, Gas Cylinders and Parts subjected to pressure..



Test Pressure :
35 Kg./Cm² to 1000 Kg./Cm²